

Instruction Sheet No. 5: Terms and Conditions of Delivery of REMONDIS SAVA GmbH

Pumpable Sludges

In addition: Appendix to the Instruction Sheets No. 1, 2, 3 and 5: Materials that are not suitable for the bunker, shredder or paste (Exclusion List)

In advance of each delivery a detailed waste description in English or German language has to be provided (current analysis, safety data sheet). Likewise, a representative sample of the waste may be submitted. Please contact us in case of deviations from the conditions specified herein!

Consistency of the waste: pasty, liquid

Possible delivery systems:

- _ Tanker or vacuum tanker
- _ ASF-container
- _ ASP-container
- _ Plastic IBC (dischargeable; with a maximum of 250 kg of non-dischargeable residue after discharge)
- _ For the delivery of flammable liquids in containers this packaging material must be electrically conductive and permitted according to ATEX
- _ Electrically conductive stretch films (ESD: Electrostatic Discharge) are to be used for wrapping in drums on pallets

Delivery Conditions (please contact us in case of deviations):

- _ Mercury < 3 ppm (or mg/kg)
- _ Sulphur < 1.0 %
- _ Zinc < 1.0 %
- _ Organically bound silicon < 0.5 %
- _ Phosphorus < 1.0 %
- _ Fluorine < 0.1 %
- _ pH value > 4
- _ The waste must not react and not solidify (flocculation, polymerisation, polycondensation) and must remain pumpable if the temperature drops (observe the setting point)
- _ The waste must be fully pumpable and drain from the container without assistance, sediment content < 30 %
- _ No foreign materials such as rags, wood, foils or similarly coarse impurities
- _ In case of liquid waste 10 % of a container's volume have to be left as expansion volume
- _ Maximum weight of a pallet or an IBC: 1,500 kg
- _ Labelling of containers according to legal requirements
- _ The identification of the containers and their assignment to the accompanying documents must be possible

Excluded from the acceptance in the cassette for pasty sludges are substances that are not suitable for the bunker due to their risk potential. For this the Appendix to the Instruction Sheets No. 1, 2, 3 and 5: Materials that are not suitable for the bunker, shredder or paste (Exclusion List) has to be observed. Those are, for example, dusty, reactive, smelling, toxic substances. These substances – appropriately packed – can be accepted for the drum lift (see Instruction Sheet No. 4).

Completely excluded from the acceptance and not permitted are gaseous, explosive and radioactive substances, likewise chemical and biological warfare agents, genetically modified materials, as well as asbestos and carbon fibre reinforced plastics.

For further information please contact:

REMONDIS SAVA GmbH // Ostertweute 1 // 25541 Brunsbüttel // Germany // T +49 4852 8308-0 // info.sava@remondis.de // remondis-sava.com

May 2025 Page 1 of 1